



NuMex PE4710 IPS Line Pipe
ASTM D 3035 IPS (Iron Pipe Size), NSF Approved NSF-pw
DR-PR (Dimension Ratio-Pressure Rated)
Based on Controlled Outside Diameter

Dimension Ratio DR-17											
Nominal Size (inches)	Pressure Rating (psi @ 73.4°F water)	Nominal Outside Diameter (inches)	Minimum Wall Thickness (inches)	Weight per 100 feet (pounds)	100' coil length	300' coil length	500' coil length	1000' coil length	1500' coil length	2000' coil length	2500' coil length
3/4	125	1.050	0.062	8.0	x	x	x	x	-	-	-
1	125	1.315	0.077	12.5	x	x	x	x	-	-	-
1 1/4	125	1.660	0.098	19.9	x	x	x	x	x	-	-
1 1/2	125	1.900	0.112	26.1	x	x	x	x	x	-	-
2	125	2.375	0.140	40.7	x	x	x	x	x	-	-
2 1/2	125	2.875	0.169	59.7	x	x	x	x	-	-	-
3	125	3.500	0.206	92.9	x	x	x	x	-	-	-

Dimension Ratio DR-15.5											
Nominal Size (inches)	Pressure Rating (psi @ 73.4°F water)	Nominal Outside Diameter (inches)	Minimum Wall Thickness (inches)	Weight per 100 feet (pounds)	100' coil length	300' coil length	500' coil length	1000' coil length	1500' coil length	2000' coil length	2500' coil length
3/4	138	1.050	0.068	8.7	x	x	x	x	-	-	-
1	138	1.315	0.084	13.6	x	x	x	x	-	-	-
1 1/4	138	1.660	0.107	21.7	x	x	x	x	x	x	-
1 1/2	138	1.900	0.123	28.4	x	x	x	x	x	x	-
2	138	2.375	0.153	44.4	x	x	x	x	x	x	-
2 1/2	138	2.875	0.185	65.0	x	x	x	x	-	-	-
3	138	3.500	0.226	96.4	x	x	x	x	-	-	-

Dimension Ratio DR-13.5											
Nominal Size (inches)	Pressure Rating (psi @ 73.4°F water)	Nominal Outside Diameter (inches)	Minimum Wall Thickness (inches)	Weight per 100 feet (pounds)	100' coil length	300' coil length	500' coil length	1000' coil length	1500' coil length	2000' coil length	2500' coil length
3/4	160	1.050	0.078	9.9	x	x	x	x	-	-	-
1	160	1.315	0.097	15.5	x	x	x	x	-	-	-
1 1/4	160	1.660	0.123	24.6	x	x	x	x	x	x	x
1 1/2	160	1.900	0.141	32.3	x	x	x	x	x	x	x
2	160	2.375	0.176	50.4	x	x	x	x	x	x	-
2 1/2	160	2.875	0.213	73.9	x	x	x	x	-	-	-
3	160	3.500	0.259	109.5	x	x	x	x	-	-	-

SDR pipe is now referred to as DR pipe in accordance with ASTM D 3035-14.



NuMex PE4710 IPS Line Pipe
ASTM D 3035 IPS (Iron Pipe Size), NSF Approved NSF-pw
DR-PR (Dimension Ratio-Pressure Rated)
Based on Controlled Outside Diameter

Dimension Ratio DR-11												
Nominal Size (inches)	Pressure Rating (psi @ 73.4°F water)	Nominal Outside Diameter (inches)	Minimum Wall Thickness (inches)	Weight per 100 feet (pounds)	100' coil length	300' coil length	500' coil length	1000' coil length	1500' coil length	2000' coil length	2500' coil length	3000' coil length
3/4	200	1.050	0.095	12.3	x	x	x	x	-	-	-	-
1	200	1.315	0.120	19.4	x	x	x	x	-	-	-	-
1 1/4	200	1.660	0.151	30.9	x	x	x	x	x	x	x	x
1 1/2	200	1.900	0.173	40.5	x	x	x	x	x	x	x	-
2	200	2.375	0.216	63.0	x	x	x	x	x	x	-	-
2 1/2	200	2.875	0.261	93.0	x	x	x	x	-	-	-	-
3	200	3.500	0.318	136.0	x	x	x	x	-	-	-	-

Dimension Ratio DR-9												
Nominal Size (inches)	Pressure Rating (psi @ 73.4°F water)	Nominal Outside Diameter (inches)	Minimum Wall Thickness (inches)	Weight per 100 feet (pounds)	100' coil length	300' coil length	500' coil length	1000' coil length	1500' coil length	2000' coil length	2500' coil length	3000' coil length
3/4	250	1.050	0.117	14.6	x	x	x	x	-	-	-	-
1	250	1.315	0.146	22.9	x	x	x	x	-	-	-	-
1 1/4	250	1.660	0.184	36.4	x	x	x	x	x	x	x	x
1 1/2	250	1.900	0.211	48.1	x	x	x	x	x	x	x	-
2	250	2.375	0.264	74.4	x	x	x	x	x	-	-	-
2 1/2	250	2.875	0.319	110.1	x	x	x	x	-	-	-	-
3	250	3.500	0.389	165.0	x	x	x	x	-	-	-	-

Dimension Ratio DR-7												
Nominal Size (inches)	Pressure Rating (psi @ 73.4°F water)	Nominal Outside Diameter (inches)	Minimum Wall Thickness (inches)	Weight per 100 feet (pounds)	100' coil length	300' coil length	500' coil length	1000' coil length	1500' coil length	2000' coil length	2500' coil length	3000' coil length
1	333	1.315	0.188	28.6	x	x	x	x	-	-	-	-
1 1/4	333	1.660	0.237	45.4	x	x	x	x	x	x	x	-
1 1/2	333	1.900	0.271	59.9	x	x	x	x	x	x	-	-
2	333	2.375	0.339	93.3	x	x	x	x	-	-	-	-
2 1/2	333	2.875	0.411	136.8	x	x	x	-	-	-	-	-
3	333	3.500	0.500	205.0	x	x	x	-	-	-	-	-

SDR pipe is now referred to as DR pipe in accordance with ASTM D 3035-14.



NuMex PE4710 IPS Line Pipe
ASTM D 3035 IPS (Iron Pipe Size), NSF Approved NSF-pw
DR-PR (Dimension Ratio-Pressure Rated)
Based on Controlled Outside Diameter

Dimension Ratio DR-6												
Nominal Size (inches)	Pressure Rating (psi @ 73.4°F water)	Nominal Outside Diameter (inches)	Minimum Wall Thickness (inches)	Weight per 100 feet (pounds)	100' coil length	300' coil length	500' coil length	1000' coil length	1500' coil length	2000' coil length	2500' coil length	3000' coil length
1	400	1.315	0.219	32.0	x	x	x	x	-	-	-	-
1 1/4	400	1.660	0.277	49.0	x	x	x	x	-	-	-	-
1 1/2	400	1.900	0.317	65.0	x	x	x	x	-	-	-	-
2	400	2.375	0.396	102.0	x	x	x	-	-	-	-	-
2 1/2	400	2.875	0.479	150.0	x	x	x	-	-	-	-	-

Dimension Ratio DR-5												
Nominal Size (inches)	Pressure Rating (psi @ 73.4°F water)	Nominal Outside Diameter (inches)	Minimum Wall Thickness (inches)	Weight per 100 feet (pounds)	100' coil length	300' coil length	500' coil length	1000' coil length	1500' coil length	2000' coil length	2500' coil length	3000' coil length
1	500	1.315	0.263	36.0	x	x	x	x	-	-	-	-
1 1/4	500	1.660	0.332	57.0	x	x	x	x	-	-	-	-
1 1/2	500	1.900	0.380	75.0	x	x	x	x	x	x	x	x
2	500	2.375	0.475	118.0	x	x	x	x	x	x	x	-
2 1/2	500	2.875	0.575	172.0	x	x	x	x	x	-	-	-

SDR pipe is now referred to as DR pipe in accordance with ASTM D 3035-14.