



NuMex PE4710

250 psi Water Service Line Tubing

**ASTM D 2737 Polyethylene (PE) Plastic Tubing, NSF Approved NSF-pw
SDR-PR (Standard Dimension Ratio-Pressure Rated), Copper Tubing Size (C.T.S.)
Based on Controlled Outside Diameter**

Standard Dimension Ratio SDR-9 C.T.S.									
Nominal Size (inches)	Pressure Rating (psi @ 73.4°F water)	Nominal Outside Diameter (inches)	Approx Inside Diameter (inches)	Approx Wall Thickness (inches)	Weight per 100 feet (pounds)	100' coil length	200' coil length	300' coil length	500' coil length
3/4	250	0.875	0.671	0.102	10.3	x	-	x	x
1	250	1.125	0.865	0.130	16.9	x	-	x	-
1 1/4	250	1.375	1.060	0.158	25.0	x	-	x	x
1 1/2	250	1.625	1.250	0.186	34.8	x	-	x	x
2	250	2.125	1.640	0.242	59.4	x	x	x	-

NuMex PE4710

250 psi Water Service Line Pipe

**ASTM D 2239 Polyethylene (PE) Plastic Pipe, NSF Approved NSF-pw
SIDR-PR (Standard Inside Dimension Ratio-Pressure Rated)**

Standard Inside Dimension Ratio SIDR-7												
Nominal Size (inches)	Pressure Rating (psi @ 73.4°F water)	Nominal Inside Diameter (inches)	Minimum Wall Thickness (inches)	Weight per 100 feet (pounds)	100' coil length	200' coil length	300' coil length	400' coil length	500' coil length	1000' coil length	1500' coil length	2000' coil length
3/4	250	0.824	0.118	15.0	x	-	x	x	x	x	-	-
1	250	1.049	0.150	24.3	x	-	x	x	x	x	-	-
1 1/4	250	1.380	0.197	41.8	x	-	x	-	x	x	x	x
1 1/2	250	1.610	0.230	56.9	x	-	x	-	x	x	x	x
2	250	2.067	0.295	93.8	x	x	x	-	x	x	x	-